



Single sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of > 500 cd/m<sup>2</sup>.

**Technical data**

<b>Viewing distance:</b>	20 m
<b>Material:</b>	Aluminium
<b>Illuminant:</b>	1 x 1W LED-module
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	16 mA
<b>Nominal current DC:</b>	14 mA


<b>Apparent power:</b>	3,6 VA
<b>Effective power:</b>	3,1 W
<b>Inrush current:</b>	6 A / 22 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C

**Available colours** Add colour code to the article no. e.g. 800 014 LXX

Special colour: L99

**Articles**

<b>SNP 7186 FLD 230V</b>	Art. no. 811 014
Wall mounting	Light colour: 6500 K Protection category: IP40



Name	Accessories	Art. no.
Legend panel 7x86 / 2420 PRO	required	714 360
Legend panel 7x86 / 2420 PLO	required	714 359
Legend panel 7x86 / 2420 PRU	required	714 358
Legend panel 7x86 / 2420 PLU	required	714 357
Legend panel 7x86 / 2420 PO	required	714 311
Legend panel 7x86 / 2420 PR	required	714 047
Legend panel 7x86 / 2420 PL	required	714 046
Legend panel 7x86 / 2420 PU	required	714 045

**Info:** When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

