



Single sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of  $> 500 \text{ cd/m}^2$ .

#### Technical data

|                            |                   |                            |  |
|----------------------------|-------------------|----------------------------|--|
| <b>Viewing distance:</b>   | 20 m              | <b>Nominal current DC:</b> | 80 mA                                  |
| <b>Material:</b>           | Aluminium         | <b>Protection class:</b>   | III                                    |
| <b>Illuminant:</b>         | 1 x 1W LED-module | <b>Input terminals:</b>    | 2.5mm <sup>2</sup> feed through wiring |
| <b>Nominal voltage DC:</b> | 24 V $\pm 20 \%$  | <b>Temperature ta:</b>     | -15...+40 °C                           |


**Available colours** Add colour code to the article no. e.g. 800 014 **LXX**

Special colour: **L99** 🌈

#### Articles

**SNP 7186 LED 24V** Art. no. 810 021

Wall mounting Light colour: 6500 K Protection category: IP40



| Name                         | Accessories | Art. no. |
|------------------------------|-------------|----------|
| Legend panel 7x86 / 2420 PRO | required    | 714 360  |
| Legend panel 7x86 / 2420 PLO | required    | 714 359  |
| Legend panel 7x86 / 2420 PRU | required    | 714 358  |
| Legend panel 7x86 / 2420 PLU | required    | 714 357  |
| Legend panel 7x86 / 2420 PO  | required    | 714 311  |
| Legend panel 7x86 / 2420 PR  | required    | 714 047  |
| Legend panel 7x86 / 2420 PL  | required    | 714 046  |
| Legend panel 7x86 / 2420 PU  | required    | 714 045  |

**Info:** When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

