



Single sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of > 500 cd/m².

Technical data


Viewing distance:	20 m	Nominal current DC:	12 mA
Material:	Aluminium	Apparent power:	5,0 VA
Illuminant:	1 x 1W LED-module	Inrush current:	8 A / 50 µs
Nominal voltage AC:	230V ±10% 50/60 Hz	Protection class:	I
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	22 mA	Temperature ta:	-15...+40 °C

Available colours Add colour code to the article no. e.g. 800 014 LXX

Special colour: L99

Articles

SNP 7186 LED J/SV	Art. no. 807 342
Wall mounting	Light colour: 6500 K Protection category: IP40



Name	Accessories	Art. no.
Legend panel 7x86 / 2420 PRO	required	714 360
Legend panel 7x86 / 2420 PLO	required	714 359
Legend panel 7x86 / 2420 PRU	required	714 358
Legend panel 7x86 / 2420 PLU	required	714 357
Legend panel 7x86 / 2420 PO	required	714 311
Legend panel 7x86 / 2420 PR	required	714 047
Legend panel 7x86 / 2420 PL	required	714 046
Legend panel 7x86 / 2420 PU	required	714 045

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

