



Single sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of $> 500 \text{ cd/m}^2$.

Technical data


Viewing distance:	35 m	Nominal current DC:	115 mA
Material:	Aluminium	Protection class:	III
Illuminant:	2 x 1W LED-module	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V \pm 20 %	Temperature ta:	-15...+40 °C

Available colours Add colour code to the article no. e.g. 800 014 **LXX**

Special colour: **L99** 🌈

Articles

SNP 7188 LED 24V	Art. no. 810 046
Wall mounting	Light colour: 6500 K Protection category: IP40



Name	Accessories	Art. no.
Legend panel 7x88/2435 PRO	required	714 362
Legend panel 7x88/2435 PLO	required	714 361
Legend panel 7x88/2435 PRU	required	714 275
Legend panel 7x88/2435 PLU	required	714 274
Legend panel 7x88 / 2435 PO	required	714 075
Legend panel 7x88 / 2435 PR	required	714 020
Legend panel 7x88 / 2435 PL	required	714 019
Legend panel 7x88 / 2435 PU	required	714 018

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

