



Single sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of  $> 500 \text{ cd/m}^2$ .

#### Technical data


|                            |                          |                            |  |
|----------------------------|--------------------------|----------------------------|--|
| <b>Viewing distance:</b>   | 35 m                     | <b>Nominal current DC:</b> | 18 mA                                  |
| <b>Material:</b>           | Aluminium                | <b>Apparent power:</b>     | 6,1 VA                                 |
| <b>Illuminant:</b>         | 2 x 1W LED-module        | <b>Inrush current:</b>     | 8 A / 50 $\mu\text{s}$                 |
| <b>Nominal voltage AC:</b> | 230V $\pm 10\%$ 50/60 Hz | <b>Protection class:</b>   | I                                      |
| <b>Nominal voltage DC:</b> | 176 - 264 V              | <b>Input terminals:</b>    | 2.5mm <sup>2</sup> feed through wiring |
| <b>Nominal current AC:</b> | 27 mA                    | <b>Temperature ta:</b>     | -15...+40 °C                           |

**Available colours** Add colour code to the article no. e.g. 800 014 LXX

Special colour: L99

#### Articles

| SNP 7188 LED J/SV | Art. no. 807 372                               |
|-------------------|--|
| Wall mounting     | Light colour: 6500 K Protection category: IP40 |



| Name                        | Accessories | Art. no. |
|-----------------------------|-------------|----------|
| Legend panel 7x88/2435 PRO  | required    | 714 362  |
| Legend panel 7x88/2435 PLO  | required    | 714 361  |
| Legend panel 7x88/2435 PRU  | required    | 714 275  |
| Legend panel 7x88/2435 PLU  | required    | 714 274  |
| Legend panel 7x88 / 2435 PO | required    | 714 075  |
| Legend panel 7x88 / 2435 PR | required    | 714 020  |
| Legend panel 7x88 / 2435 PL | required    | 714 019  |
| Legend panel 7x88 / 2435 PU | required    | 714 018  |

**Info:** When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

