



Single sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of  $> 500 \text{ cd/m}^2$ .

### Technical data

<b>Viewing distance:</b>	35 m	<b>Apparent power:</b>	6,1 VA
<b>Material:</b>	Aluminium	<b>Inrush current:</b>	8 A / 50 $\mu\text{s}$
<b>Illuminant:</b>	2 x 1W LED-module	<b>Protection class:</b>	I
<b>Nominal voltage AC:</b>	230V AC $\pm 10\%$ 50/60 Hz	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal current AC:</b>	27 mA	<b>Temperature ta:</b>	-15...+40 °C


**Available colours** Add colour code to the article no. e.g. 800 014 LXX

Special colour: L99

### Articles

**SNP 7188 LED NE/SV** Art. no. 807 382

Wall mounting Light colour: 6500 K Protection category: IP40



Name	Accessories	Art. no.
Legend panel 7x88/2435 PRO	required	714 362
Legend panel 7x88/2435 PLO	required	714 361
Legend panel 7x88/2435 PRU	required	714 275
Legend panel 7x88/2435 PLU	required	714 274
Legend panel 7x88 / 2435 PO	required	714 075
Legend panel 7x88 / 2435 PR	required	714 020
Legend panel 7x88 / 2435 PL	required	714 019
Legend panel 7x88 / 2435 PU	required	714 018

**Info:** When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

