




Double-sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of $> 500 \text{ cd/m}^2$.

Technical data


viewing distance:	60 m	Effective power:	9,6 W
Material:	aluminium	Protection class:	III
Illuminant:	8 x 1W LED-module	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V \pm 20 %	Temperature ta:	-15...+40 °C
Nominal current DC:	400 mA		

Articles

SNP 7260 D LED 24V	
Colors	Aluminium
Art. no.	101362875
ceiling mounting	Light colour: 6500 K Protection category: IP40



SNP 7260 K LED 24V	
Colors	Aluminium
Art. no.	101362976
chain mounting	Light colour: 6500 K Protection category: IP40



Name	Accessories	Art. no.
Blind cover 7x60 grey	optional	102003176
L-JET 3 - max. 24V DC, 320mAconst	spare part	101421176
Legend panel 7x60 PL	required	101950232
Legend panel 7x60 PO	required	101950030
Legend panel 7x60 PR	required	101950131
Legend panel 7x60 PU	required	101950333
Legend panel 7x60 custom design		101871218
Piktogrammscheibe 7x60hochkant Sonder n. Vorgabe	optional	104822846

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

