



Double-sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of $> 500 \text{ cd/m}^2$.


Technical data

viewing distance:	60 m	Apparent power:	14,0 VA
Material:	aluminium	Effective power:	13,0 W
Illuminant:	8 x 1W LED-module	Inrush current:	8 A / 50 μs
Nominal voltage AC:	230V $\pm 10\%$ 50/60 Hz	Protection class:	I
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	61 mA	Temperature ta:	-15...+40 °C
Nominal current DC:	60 mA		

Articles


SNP 7260 D LED J/SV

Colors	Aluminium
Art. no.	101291238
ceiling mounting	Light colour: 6500 K Protection category: IP40



SNP 7260 K LED J/SV

Colors	Aluminium
Art. no.	101291339
chain mounting	Light colour: 6500 K Protection category: IP40



Name	Accessories	Art. no.
Blind cover 7x60 grey	optional	102003176
J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267
Legend panel 7x60 PL	required	101950232
Legend panel 7x60 PO	required	101950030
Legend panel 7x60 PR	required	101950131
Legend panel 7x60 PU	required	101950333
Legend panel 7x60 custom design		101871218
Piktogrammscheibe 7x60hochkant Sonder n. Vorgabe	optional	104822846

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

