



Double-sided aluminium profile emergency exit luminaires with additional light output at bottom side. Homogeneous illumination by state-of-the-art LED technology with a luminance of > 500 cd/m².

Technical data


Viewing distance:	12 m	Nominal current DC:	18 mA
Material:	Aluminium	Apparent power:	6,1 VA
Illuminant:	2 x 1W LED-module	Inrush current:	8 A / 50 µs
Nominal voltage AC:	230V ±10% 50/60 Hz	Protection class:	I
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	27 mA	Temperature ta:	-15...+40 °C

Available colours Add colour code to the article no. e.g. 800 014 **LXX**

Special colour: **L99**

Articles

SNP 7284 D LED J/SV	Art. no. 807 544
Ceiling mounting	Light colour: 6500 K Protection category: IP40



Name	Accessories	Art. no.
Legend panel 7x84 PLO without logo	required	714 341
Legend panel 7x84 PRO without logo	required	714 340
Legend panel 7x84 PLU without logo	required	714 339
Legend panel 7x84 PRU without logo	required	714 338
Legend panel 7x84 PO without logo	required	714 337
Legend panel 7x84 PU without logo	required	714 059
Legend panel 7x84 PR without logo	required	714 058
Legend panel 7x84 PL without logo	required	714 057
Blind cover 7x84 / 7x12 grey	required	704 924
opal cover 7x84	required	704 056

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

