



Cubic emergency exit luminaires made of aluminium profile. Homogeneous illumination by state-of-the-art LED technology with a luminance of  $> 500 \text{ cd/m}^2$ .


### Technical data

<b>Viewing distance:</b>	35 m	<b>Nominal current DC:</b>	200 mA
<b>Material:</b>	Aluminium	<b>Protection class:</b>	III
<b>Illuminant:</b>	4 x 1W LED-module	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal voltage DC:</b>	24 V $\pm$ 20 %	<b>Temperature ta:</b>	-15...+40 °C

### Articles


#### SNP 7460 D LED 24V Art. no. 810 071

Wall or ceiling mounting    Light colour: 6500 K    Protection category: IP40




#### SNP 7460 K LED 24V Art. no. 810 090

Chain mounting    Light colour: 6500 K    Protection category: IP40



#### SNP 7460 P LED 24V Art. no. 810 089

Pendulum mounting    Light colour: 6500 K    Protection category: IP40



Name	Accessories	Art. no.
cover SNP 7460 ceiling mounting ISO 7010	required	893 271
cover SNP 7460 D PL/PU/PR/opal ISO 7010	required	893 216
Pendulum SN-luminaire 24 V 2,0 m gr	required	890 539
Pendulum SN-luminaire 24 V 2,0 m ws	required	890 538
Pendulum SN-luminaire 24 V 1,0 m gr	required	890 537
Pendulum SN-luminaire 24 V 1,0 m ws	required	890 536
Pendulum SN-luminaire 24 V 0,5 m gr	required	890 535
Pendulum SN-luminaire 24 V 0,5 m ws	required	890 534

**Info:** When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

For luminaires with pendulum mounting, select the desired pendulum (length and colour of baldachin).

