



Double-sided ball-impact and shock resistant exit-luminaire. Powder-coated metal housing with slim design and brilliant pictograph illumination > 500cd/m². Perfect for use in environments with high mechanical stresses and in sports facilities.




Technical data

viewing distance:	30 m
Material:	sheet steel powder-coated
Illuminant:	4 x 1W LED-module
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	30 mA
Nominal current DC:	27 mA

Apparent power:	7,0 VA
Effective power:	5,1 W
Inrush current:	6 A / 34 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10

Articles

SNP 8030 D FLD 230V			
Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101376922	101376821	101377023
ceiling mounting	Light colour: 6500 K		Protection category: IP40



Name	Accessories	Art. no.
Cover 8030 opal	required	101205150
FLD 230/4 - CC - 320 - L	spare part	101965083
Legend panel 8030 PL	required	101224449
Legend panel 8030 PO	required	101225459
Legend panel 8030 PR	required	101224550
Legend panel 8030 PU	required	101224651
Legend panel SNP 8030 PLO	required	101225661
Legend panel SNP 8030 PLU	required	101225055
Legend panel SNP 8030 PRO	required	101225762
Legend panel SNP 8030 PRU	required	101225156
special pictogram 8030	required	101225257

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

