

**230V****SNP 8030 D** Ball-impact and shock resistant safety luminaires**NE/SV**

For connection to INOTEC-NEA-monitoring systems



Double-sided ball-impact and shock resistant exit-luminaire. Powder-coated metal housing with slim design and brilliant pictograph illumination  $> 500\text{cd/m}^2$ . Perfect for use in environments with high mechanical stresses and in sports facilities.


**Technical data**

<b>viewing distance:</b>	30 m
<b>Material:</b>	sheet steel powder-coated
<b>illuminant:</b>	4 x 1W LED-module
<b>Nominal voltage AC:</b>	230V AC $\pm 10\%$ 50/60 Hz
<b>Nominal current AC:</b>	36 mA
<b>Apparent power:</b>	8,3 VA

<b>Effective power:</b>	7,4 W
<b>Inrush current:</b>	8 A / 50 $\mu\text{s}$
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C
<b>Impact resistance:</b>	IK10

**Articles**

SNP 8030 D LED NE/SV			
Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101312557	101312456	101312658
ceiling mounting	Light colour: 6500 K	Protection category: IP40	



Name	Accessories	Art. no.
Cover 8030 opal	required	101205150
Legend panel 8030 PL	required	101224449
Legend panel 8030 PO	required	101225459
Legend panel 8030 PR	required	101224550
Legend panel 8030 PU	required	101224651
Legend panel SNP 8030 PLO	required	101225661
Legend panel SNP 8030 PLU	required	101225055
Legend panel SNP 8030 PRO	required	101225762
Legend panel SNP 8030 PRU	required	101225156
NE - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420570
special pictogram 8030	required	101225257

**Info:** When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

