



Single sided ball-impact and shock resistant exit luminaire. Powder-coated aluminium housing with slim design and brilliant pictograph illumination > 500cd/m². Perfect for use in environments with high mechanical stresses and in sports facilities.



Technical data



viewing distance:	30 m
Material:	sheet steel powder-coated
illuminant:	2 x 1W LED-module
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	26 mA
Nominal current DC:	17 mA

Apparent power:	5,9 VA
Effective power:	3,7 W
Inrush current:	6 A / 34 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10

Articles

SNP 8030 FLD 230V			
Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101376316	101376215	101376417
wall mounting	Light colour: 6500 K		Protection category: IP40

SNP 8030 WE FLD 230V			
Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101376619	101376518	101376720
recessed wall mounting	Light colour: 6500 K		Protection category: IP40



Name	Accessories	Art. no.
2 REBEL 100LM KWS 185X21,5KB 90MM OPTIK	spare part	092283
FLD 230/4 - CC - 320 - L	spare part	101965083
Legend panel 8030 PL	required	101224449
Legend panel 8030 PO	required	101225459
Legend panel 8030 PR	required	101224550
Legend panel 8030 PU	required	101224651
Legend panel 8030 WE PL	required	101224752
Legend panel 8030 WE PO	required	101225560
Legend panel 8030 WE PR	required	101224853
Legend panel 8030 WE PU	required	101224954
Legend panel SNP 8030 PLO	required	101225661
Legend panel SNP 8030 PLU	required	101225055
Legend panel SNP 8030 PRO	required	101225762
Legend panel SNP 8030 PRU	required	101225156
Legend panel SNP 8030 WE - custom design	required	101225358
special pictogram 8030	required	101225257

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

