



Single sided ball-impact and shock resistant exit luminaire. Powder-coated aluminium housing with slim design and brilliant pictograph illumination > 500cd/m². Perfect for use in environments with high mechanical stresses and in sports facilities.

Makrolon pictogram for high impact resistance IK10+ (50 joules) available as an option.



Technical data



viewing distance:	30 m
Material:	sheet steel powder-coated
illuminant:	2 x 1W LED-module
Nominal voltage DC:	24 V ±20 %
Nominal current DC:	115 mA

Protection class:	III
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10

Articles

SNP 8030 LED 24V			
Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101335492	101335391	101335593
wall mounting	Light colour: 6500 K	Protection category:	IP40

SNP 8030 WE LED 24V			
Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101335795	101335694	101335896
recessed wall mounting	Light colour: 6500 K	Protection category:	IP40



Name	Accessories	Art. no.
Legend panel 8030 PL	required	101224449
Legend panel 8030 PO	required	101225459
Legend panel 8030 PR	required	101224550
Legend panel 8030 PU	required	101224651
Legend panel 8030 WE PL	required	101224752
Legend panel 8030 WE PO	required	101225560
Legend panel 8030 WE PR	required	101224853
Legend panel 8030 WE PU	required	101224954
Legend panel SNP 8030 PLO	required	101225661
Legend panel SNP 8030 PLU	required	101225055
Legend panel SNP 8030 PRO	required	101225762
Legend panel SNP 8030 PRU	required	101225156

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

