

230V

SNP 808 Stainless steel luminaires

For connection to FUSION central battery- or emergency power (NEA) systems



Single sided emergency exit luminaires made of robust, brushed stainless steel with high protection category. Homogeneous illumination by state-of-the-art LED technology with a luminance of $>500\text{cd/m}^2$. Suitable for use in food industry or food processing plants with high demands on product hygiene.

Makrolon pictogram for high impact resistance IK10+ (50 joules) available as an option.


**Technical data**

viewing distance:	30 m
Material:	stainless steel brushed
illuminant:	2 x 1W LED-module
Nominal voltage AC:	230V $\pm 10\%$ 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	19 mA
Nominal current DC:	18 mA

Apparent power:	4,4 VA
Effective power:	4,0 W
Inrush current:	6 A / 22 μs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10

Articles**SNP 808 FLD 230V**

Colors	stainless steel	HWF 7015	RAL 7015	RAL 9016	HWF 9016	HWF (special)
Art. no.	101377629	102269120	101378033	101377932	101377730	101377831
wall mounting		Light colour: 6500 K			Protection category: IP65	



Name	Accessories	Art. no.
FLD 230/8 – CC – 320 – C	Ersatzteil	100903238
LM 808 185x21,5 2/6,5K KB90	Ersatzteil	101446438
Legend panel 808 / 828 PL	required	101212325
Legend panel 808 / 828 PL without logo	required	101216365
Legend panel 808 / 828 PLO without logo	required	101216870
Legend panel 808 / 828 PLU without logo	required	101216668
Legend panel 808 / 828 PO	required	101212628
Legend panel 808 / 828 PO without logo	required	101216163
Legend panel 808 / 828 PR	required	101212426
Legend panel 808 / 828 PR without logo	required	101216466
Legend panel 808 / 828 PRO without logo	required	101216769
Legend panel 808 / 828 PRU without logo	required	101216567
Legend panel 808 / 828 PU	required	101212527
Legend panel 808 / 828 PU without logo	required	101216264
Legend panel 808 / 828, makrolon	required	101223944
Piktogrammscheibe 808 / 828Sonder	required	101223742

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

