



Single sided emergency exit luminaires made of robust, brushed stainless steel with high protection category. Homogeneous illumination by state-of-the-art LED technology with a luminance of $>500\text{cd/m}^2$. Suitable for use in food industry or food processing plants with high demands on product hygiene.

Technical data

viewing distance:	17 m
Material:	stainless steel
Illuminant:	2 x 1W LED-module
Nominal voltage AC:	230V $\pm 10\%$ 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	19 mA
Nominal current DC:	18 mA

Apparent power:	4,4 VA
Effective power:	4,0 W
Inrush current:	6 A / 22 μs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C

Articles

SNP 818 FLD 230V			
Colors	stainless steel		
Art. no.	101962558		
wall mounting	Light colour: 6500 K	Protection category: IP54	



Name	Accessories	Art. no.
FLD 230/4 - CC - 320 - L	spare part	101965083
Legend panel 818 PL	required	101217072
Legend panel 818 PR	required	101217173
Legend panel 818 PU	required	101216971

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

PO:	PR:	PU:	PL:	PRO:	PRU:	PLU:	PLO: