SNP 818 Stainless steel luminaires **24V** For connection to INOTEC systems with 24V circuits





Single sided emergency exit luminaires made of robust, brushed stainless steel with high protection category. Homogeneous illumination by state-of-the-art LED technology with a luminance of >500cd/m². Suitable for use in food industry or food processing plants with high demands on product hygiene.

Technical data


viewing distance: 17 m **Material:** stainless steel brushed Illuminant: 2 x 1W LED-module Nominal voltage DC: 24 V ±20 % Nominal current DC: 115 mA

2,8 W **Effective power:** Ш **Protection class:** Input terminals: 2.5mm² feed through wiring Temperature ta: -15...+40 °C

Articles

SNP 818 LED 24V					
Colors	stainless steel	HWF (special)	HWF (special)		
Art. no.	101333270	102178786	102062790		
wall mounting		ight colour: 6500 K	Protection category:		





Name	Accessories	Art. no.
L-JET 3 - max. 24V DC, 320mAconst	spare part	101421176
Legend panel 818 PL	required	101217072
Legend panel 818 PR	required	101217173
Legend panel 818 PU	required	101216971
special legend panel 818	required	101223843

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.













