

230V**SNP 818** Stainless steel luminaires**J/SV**

For connection to JOKER-central battery systems



Single sided emergency exit luminaires made of robust, brushed stainless steel with high protection category. Homogeneous illumination by state-of-the-art LED technology with a luminance of $>500\text{cd/m}^2$. Suitable for use in food industry or food processing plants with high demands on product hygiene.


Technical data

viewing distance:	17 m
Material:	stainless steel brushed
Illuminant:	2 x 1W LED-module
Nominal voltage AC:	230V \pm 10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	27 mA
Nominal current DC:	18 mA

Apparent power:	6,1 VA
Effective power:	5,1 W
Inrush current:	8 A / 50 μ s
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C

Articles

SNP 818 LED J/SV				
Colors	stainless steel	HWF 9016	HWF (special)	RAL (special)
Art. no.	101314274	101314476	101314577	101314678
wall mounting	Light colour: 6500 K		Protection category: IP54	



Name	Accessories	Art. no.
J - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420267
Legend panel 818 PL	required	101217072
Legend panel 818 PR	required	101217173
Legend panel 818 PU	required	101216971
opal cover 818	required	704246
special legend panel 818	required	101223843

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

