

230V**SNP 818** Stainless steel luminaires**NE/SV**

For connection to INOTEC-NEA-monitoring systems



Single sided emergency exit luminaires made of robust, brushed stainless steel with high protection category. Homogeneous illumination by state-of-the-art LED technology with a luminance of $>500\text{cd/m}^2$. Suitable for use in food industry or food processing plants with high demands on product hygiene.


Technical data

viewing distance:	17 m
Material:	stainless steel brushed
Illuminant:	2 x 1W LED-module
Nominal voltage AC:	230V AC $\pm 10\%$ 50/60 Hz
Nominal current AC:	27 mA
Apparent power:	6,1 VA

Effective power:	5,1 W
Inrush current:	8 A / 50 μs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C

Articles

SNP 818 LED NE/SV		
Colors	stainless steel	
Art. no.	101314779	
wall mounting	Light colour: 6500 K	Protection category: IP54



Name	Accessories	Art. no.
Legend panel 818 PL	required	101217072
Legend panel 818 PR	required	101217173
Legend panel 818 PU	required	101216971
NE - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420570
opal cover 818	required	704246
special legend panel 818	required	101223843

Info: When ordering an exit luminaire, the required pictogram with the corresponding arrow direction must be indicated.

