

**230V****SN 2040.1-41 Polycarbonate luminaires****J/SV**

For connection to JOKER-central battery systems




Functional LED downlight with a flat design ideal for area or escape route illumination. UV resistant, heat filament tested polycarbonate housing for ceiling mounting with optional side cable entry.

**Technical data**

<b>Material:</b>	polycarbonate
<b>Illuminant:</b>	4 x 1W LED-module
<b>Luminous flux:</b>	310 lm
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	31 mA
<b>Nominal current DC:</b>	32 mA

<b>Apparent power:</b>	7,0 VA
<b>Effective power:</b>	5,5 W
<b>Inrush current:</b>	6 A / 98 µs
<b>Protection class:</b>	II
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	[m]	[m]
2.5	3.7	8.5
3.0	4.1	9.7
4.0	4.7	11.5
5.0	5.0	12.9
6.0	5.1	13.9
7.0	4.9	14.3
8.0	4.5	14.4
9.0	3.7	14.3
10.0	2.5	13.8

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

[m]	[m]	[m]
2.5	2.7	6.4
3.0	3.1	7.3
4.0	3.6	9.0
5.0	3.7	10.6
6.0	3.7	11.8
7.0	3.6	12.4
8.0	3.4	12.8
9.0	3.1	12.6
10.0	2.6	12.4

**Articles**

SN 2040.1 -41 LED J/SV		
Colors	Polycarbonat	RAL (special)
Art. no.	101267188	101267390

Name	Accessories	Art. no.
J-ET 5.1 SV-max. 24V DC320mA const.	Ersatzteil	101422893
LM 2040.1-41 4/6,5K KB250	Ersatzteil	104429186

ceiling mounting      Light colour: 6500 K      Protection category: IP40

