

230V**SN 2040.1-41 Polycarbonate luminaires****NE/SV**

For connection to INOTEC-NEA-monitoring systems




Functional LED downlight with a flat design ideal for area or escape route illumination. UV resistant, heat filament tested polycarbonate housing for ceiling mounting with optional side cable entry.

Technical data

Material:	polycarbonate
Illuminant:	4 x 1W LED-module
Luminous flux:	310 lm
Nominal voltage AC:	230V AC \pm 10% 50/60 Hz
Nominal current AC:	36 mA
Apparent power:	8,3 VA

Effective power:	7,4 W
Inrush current:	8 A / 50 μ s
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	2.5	3.7	8.5
2.5	3.7	8.5	
3.0	4.1	9.7	
4.0	4.7	11.5	
5.0	5.0	12.9	
6.0	5.1	13.9	
7.0	4.9	14.3	
8.0	4.5	14.4	
9.0	3.7	14.3	
10.0	2.5	13.8	

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

[m]	2.5	2.7	6.4
2.5	2.7	6.4	
3.0	3.1	7.3	
4.0	3.6	9.0	
5.0	3.7	10.6	
6.0	3.7	11.8	
7.0	3.6	12.4	
8.0	3.4	12.8	
9.0	3.1	12.6	
10.0	2.6	12.4	

Articles

SN 2040.1 -41 LED NE/SV	
Colors	Polycarbonat
Art. no.	101267491

Name	Accessories	Art. no.
LM 2040.1-41 4/6,5K KB250	Ersatzteil	104429186
NE - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420570

ceiling mounting Light colour: 6500 K Protection category: IP40

