SN 2040.1-T Polycarbonate luminaires

For connection to JOKER-central battery systems

INOTEC
Sicherheitstechnik GmbH




Functional LED downlight with a flat design for mounting height up to 32m, ideal for escape route illumination. UV resistant, heat filament tested polycarbonate housing for ceiling mounting with optional side cable entry.

Technical data

Material:	polycarbonate
Illuminant:	replaceable 4 x 1W LED-module
Luminous flux:	277 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	31 mA
Nominal current DC:	32 mA

Apparent power:	7,0 VA
Effective power:	5,5 W
Inrush current:	6 A / 98 µs
Protection class:	II
Input terminals:	2.5mm² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (for an escape route with of 1m), Maintenance factor 0.8

11.0	4.6	11.0
12.0	4.7	11.5
14.0	4.9	12.4
16.0	4.9	13.1
18.0	4.9	13.6
20.0	4.5	14.1
22.0	4.3	14.2
24.0	4.3	14.3
26.0	-	14.2
28.0	-	14.1
30.0	-	13.9
32.0	-	13.6

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

11.0	3.3	9.0
12.0	3.6	9.5
14.0	3.7	10.3
16.0	3.7	11.1
18.0	3.7	11.8
20.0	3.7	12.2
22.0	3.6	12.7
24.0	3.6	12.8
26.0	3.5	12.8
28.0	3.2	12.4
30.0	3.0	12.2
32.0	2.8	12.1

Articles

SN 2040.1 T LED J/SV		
Colors	Polycarbonat	RAL (special)
Art. no.	100747735	100747836

ceiling mounting Light colour: 4000 K Protection category: IP40

Name	Accessories	Art. no.
J-ET 5.1 SV-max. 24V DC320mA const.	spare part	101422893
LM 2040.1T 4/6,5K KB250 LED Modul	spare part	104428984



