

230V**SN 2040.1-T Polycarbonate luminaires****NE/SV**

For connection to INOTEC-NEA-monitoring systems




Functional LED downlight with a flat design for mounting height up to 32m, ideal for escape route illumination. UV resistant, heat filament tested polycarbonate housing for ceiling mounting with optional side cable entry.

Technical data

Material:	polycarbonate
Illuminant:	4 x 1W LED-module
Luminous flux:	277 lm
Nominal voltage AC:	230V AC \pm 10% 50/60 Hz
Nominal current AC:	36 mA
Apparent power:	8,3 VA

Effective power:	7,4 W
Inrush current:	8 A / 50 μ s
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	1.0lx	0.8lx
11.0	4.6	11.1
12.0	4.7	11.5
14.0	4.9	12.5
16.0	5.0	13.2
18.0	5.0	13.7
20.0	5.0	14.0
22.0	4.9	14.2
24.0	4.6	14.3
26.0	4.2	14.3
28.0	3.7	14.1
30.0	2.9	14.1
32.0	0.9	13.6

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

[m]	1.0lx	0.8lx
11.0	3.3	9.0
12.0	3.6	9.5
14.0	3.7	10.3
16.0	3.7	11.1
18.0	3.7	11.8
20.0	3.7	12.2
22.0	3.6	12.7
24.0	3.6	12.8
26.0	3.5	12.8
28.0	3.2	12.4
30.0	3.0	12.2
32.0	2.8	12.1

Articles

SN 2040.1 T LED NE/SV	
Colors	Polycarbonat
Art. no.	100747937

Name	Accessories	Art. no.
LM 2040.1T 4/6,5K KB250	Ersatzteil	104428984
NE - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420570

ceiling mounting Light colour: 6500 K Protection category: IP40

