




Universal LED downlight ideal for escape route illumination. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.



Technical data

Material:	polycarbonate	Effective power:	2,2 W
Illuminant:	replaceable 4 x 0,3W LED-module	Protection class:	III
Luminous flux:	155 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C
Nominal current DC:	90 mA	Impact resistance:	IK06




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

| Beam diameter (mm) |
|--------------------|--------------------|--------------------|--------------------|--------------------|
| 2.0 | 4.4 | 10.3 | 4.5 | 1.5 |
| 2.5 | 5.1 | 11.8 | 4.6 | 1.4 |
| 3.0 | 5.6 | 13.2 | 4.3 | 1.3 |
| 3.5 | 6.1 | 14.5 | 3.9 | 1.2 |
| 4.0 | 6.5 | 15.6 | 3.6 | 1.2 |
| 4.5 | 6.9 | 16.6 | 3.6 | 1.1 |
| 5.0 | 7.2 | 17.6 | 3.5 | 1.0 |
| 5.5 | 7.3 | 18.4 | 3.4 | 0.9 |

Articles


SN 2100 B-ECO LED 24V

Colors	Polycarbonat
Art. no.	101345091
ceiling mounting	Light colour: 6500 K Protection category: IP40




SN 2100 B-ECO LED 24V

Colors	Polycarbonat
Art. no.	101345293
ceiling mounting	Light colour: 6500 K Protection category: IP65



chain mounting adapter SN 2100

Art. no. 100923042



Name	Accessories	Art. no.
L-JET 1 - max. 24V DC, 120mAconst	spare part	101420974
chain mounting adapter SN 2100	optional	100923042
clear cover SN 2100 LED	spare part	100612541