




Universal LED downlight ideal for escape route illumination. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.

Technical data

Material:	polycarbonate
Illuminant:	replaceable 4 x 1W LED-module
Luminous flux:	269 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	27 mA
Nominal current DC:	28 mA

Apparent power:	6,3 VA
Effective power:	6,0 W
Inrush current:	6 A / 22 µs
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK06





Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter (mm)	Beam diameter (mm)	Beam diameter (mm)
2.5	5.8	13.5
3.0	6.5	15.1
4.0	7.7	17.9
5.0	8.6	20.4
6.0	9.4	22.6
7.0	10.0	24.4


Articles

SN 2100 B FLD 230V		
Colors	Polycarbonat	
Art. no.	100854637	
ceiling mounting	Light colour: 6500 K	Protection category: IP40

SN 2100 B FLD 230V		
Colors	Polycarbonat	
Art. no.	100854738	
ceiling mounting	Light colour: 6500 K	Protection category: IP65



chain mounting adapter SN 2100	Art. no. 100923042
---------------------------------------	--------------------



Name	Accessories	Art. no.
FLD 230/8 – CC – 320 – C	spare part	100903238
LMC 2100 B LED Modul und Umrüstsatz	spare part	101942855
chain mounting adapter SN 2100	optional	100923042
clear cover SN 2100 LED	spare part	100612541