




Universal LED downlight ideal for escape route illumination. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.



### Technical data

<b>Material:</b>	polycarbonate	<b>Effective power:</b>	5,1 W
<b>Illuminant:</b>	replaceable 4 x 1W LED-module	<b>Protection class:</b>	III
<b>Luminous flux:</b>	269 lm	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal voltage DC:</b>	24 V ±25 %	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current DC:</b>	210 mA	<b>Impact resistance:</b>	IK06




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter (m)	Beam diameter (ft)	Beam diameter (in)
2.5	5.8	13.5
3.0	6.5	15.1
4.0	7.7	17.9
5.0	8.6	20.4
6.0	9.4	22.6
7.0	10.0	24.4

### Articles


#### SN 2100 B LED 24V

Colors	Polycarbonat
Art. no.	101340041
ceiling mounting	Light colour: 6500 K Protection category: IP40




#### SN 2100 B LED 24V

Colors	Polycarbonat	Polycarbonat
Art. no.	101340142	102280638
ceiling mounting	Light colour: 6500 K	Protection category: IP65



#### chain mounting adapter SN 2100

Art. no. 100923042



Name	Accessories	Art. no.
ILD 24/4-CC-320-C	spare part	101425321
LMC 2100 B LED Modul und Umrüstsatz	spare part	101942855
chain mounting adapter SN 2100	optional	100923042
clear cover SN 2100 LED	spare part	100612541