




Universal LED downlight ideal for area or escape route illumination. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.



Technical data

Material:	polycarbonate	Effective power:	2,2 W
Illuminant:	replaceable 4 x 0,3W LED-module	Protection class:	III
Luminous flux:	152 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C
Nominal current DC:	90 mA	Impact resistance:	IK06



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance (m)	2.0	2.8	7.0	7.1	2.8
2.0	2.0	2.8	7.0	7.1	2.8
2.5	3.0	7.7	7.7	3.0	
3.0	3.2	8.3	8.3	3.1	
3.5	3.2	8.7	8.6	3.2	
4.0	3.2	9.0	8.9	3.2	
4.5	3.1	9.1	9.1	3.0	
5.0	2.9	9.2	9.1	2.8	
5.5	2.5	9.1	9.1	2.5	
6.0	2.0	9.0	8.9	2.0	


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Distance (m)	2.5	2.1	6.7	6.8	2.2
2.5	2.5	2.1	6.7	6.8	2.2
3.0	2.1	7.3	7.4	2.1	
4.0	2.1	8.2	8.3	2.1	
5.0	2.0	8.7	8.8	2.0	
6.0	1.9	8.8	8.9	1.9	

Articles


SN 2100 ECO LED 24V

Colors	Polycarbonat
Art. no.	101344990
ceiling mounting	Light colour: 6500 K Protection category: IP40




SN 2100 ECO LED 24V

Colors	Polycarbonat
Art. no.	101345192
ceiling mounting	Light colour: 6500 K Protection category: IP65



chain mounting adapter SN 2100

Art. no. 100923042



Name	Accessories	Art. no.
L-JET 1 - max. 24V DC, 120mAconst	spare part	101420974
chain mounting adapter SN 2100	optional	100923042
clear cover SN 2100 LED	spare part	100612541