

230V SN 2100 Polycarbonate luminaires

FLD For connection to FUSION central battery- or emergency power (NEA) systems




Universal LED downlight ideal for area or escape route illumination. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.

Technical data

Material:	polycarbonate
Illuminant:	4 x 1W LED-module
Luminous flux:	338 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	27 mA
Nominal current DC:	28 mA

Apparent power:	6,3 VA
Effective power:	6,0 W
Inrush current:	6 A / 22 µs
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK06



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter [m]	2.5	4.0	10.0	10.3	4.0
2.5	4.0	10.8	11.0	4.3	
3.0	4.6	12.0	12.3	4.8	
4.0	4.7	12.8	13.1	4.9	
5.0	4.6	13.2	13.7	4.9	
6.0	4.3	13.4	13.9	4.4	
7.0	3.7	13.3	13.9	3.8	
8.0	2.5	13.0	13.3	2.7	
9.0	1.7	12.1	12.9	1.9	
10.0					

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


Beam diameter [m]	2.5	2.7	8.4	8.5	2.7
2.5	2.9	9.1	9.2	2.9	
3.0	3.0	10.4	10.5	3.0	
4.0	3.0	11.5	11.6	3.0	
5.0	3.0	12.3	12.4	3.0	
6.0	3.2	12.5	12.6	3.2	
7.0	3.1	12.5	12.6	3.1	
8.0	2.8	12.2	12.1	2.8	
9.0	2.3	12.0	12.1	2.3	
10.0					

Articles

SN 2100 FLD 230V

Colors	Polycarbonat
Art. no.	100854435


ceiling mounting Light colour: 6500 K Protection category: IP40



SN 2100 FLD 230V


Colors	Polycarbonat	RAL (special)
Art. no.	100854536	104248728

ceiling mounting Light colour: 6500 K Protection category: IP65



chain mounting adapter SN 2100

Art. no. 100923042



Name	Accessories	Art. no.
FLD 230/8 – CC – 320 – C	Ersatzteil	100903238
LED replacement kit SN 2100	Ersatzteil	101942754
chain mounting adapter SN 2100	optional	100923042
clear cover SN 2100 LED	Ersatzteil	100612541