




Universal LED downlight ideal for area or escape route illumination. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.



### Technical data

<b>Material:</b>	polycarbonate	<b>Protection class:</b>	III
<b>Illuminant:</b>	4 x 1W LED-module	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Luminous flux:</b>	338 lm	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal voltage DC:</b>	24 V ±25 %	<b>Impact resistance:</b>	IK06
<b>Nominal current DC:</b>	210 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

[m]	2.5	4.0	10.0	10.3	4.0
2.5	4.0	10.0	10.3	4.0	
3.0	4.3	10.8	11.0	4.3	
4.0	4.6	12.0	12.3	4.8	
5.0	4.7	12.8	13.1	4.9	
6.0	4.6	13.2	13.7	4.9	
7.0	4.3	13.4	13.9	4.4	
8.0	3.7	13.3	13.9	3.8	
9.0	2.5	13.0	13.3	2.7	
10.0	1.7	12.1	12.9	1.9	

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


[m]	2.5	2.7	8.4	8.5	2.7
2.5	2.7	8.4	8.5	2.7	
3.0	2.9	9.1	9.2	2.9	
4.0	3.0	10.4	10.5	3.0	
5.0	3.0	11.5	11.6	3.0	
6.0	3.0	12.3	12.4	3.0	
7.0	3.2	12.5	12.6	3.2	
8.0	3.1	12.5	12.6	3.1	
9.0	2.8	12.2	12.1	2.8	
10.0	2.3	12.0	12.1	2.3	

### Articles

#### SN 2100 LED 24V

Colors	Polycarbonat	RAL (special)
Art. no.	101339435	101339536


ceiling mounting      Light colour: 6500 K      Protection category: IP40



#### SN 2100 LED 24V


Colors	Polycarbonat	RAL (special)
Art. no.	101339738	101339839

ceiling mounting      Light colour: 6500 K      Protection category: IP65



#### chain mounting adapter SN 2100

Art. no. 100923042



Name	Accessories	Art. no.
ILD 24/4-CC-320-C	Ersatzteil	101425321
LED replacement kit SN 2100	Ersatzteil	101942754
chain mounting adapter SN 2100	optional	100923042
clear cover SN 2100 LED	Ersatzteil	100612541