

230V

SN 2100 Polycarbonate luminaires

J/SV

For connection to JOKER-central battery systems




Universal LED downlight ideal for area or escape route illumination. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.



Technical data

Material:	polycarbonate
Illuminant:	4 x 1W LED-module
Luminous flux:	338 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	36 mA
Nominal current DC:	32 mA

Apparent power:	8,3 VA
Effective power:	7,4 W
Inrush current:	8 A / 50 µs
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK06



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Height [m]	2.5	4.0	10.0	10.3	4.0
2.5	4.0	10.8	11.0	4.3	
3.0	4.6	12.0	12.3	4.8	
4.0	4.7	12.8	13.1	4.9	
5.0	4.6	13.2	13.7	4.9	
6.0	4.3	13.4	13.9	4.4	
7.0	3.7	13.3	13.9	3.8	
8.0	2.5	13.0	13.3	2.7	
9.0	1.7	12.1	12.9	1.9	
10.0					

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


Height [m]	2.5	2.7	8.4	8.5	2.7
2.5	2.9	9.1	9.2	2.9	
3.0	3.0	10.4	10.5	3.0	
4.0	3.0	11.5	11.6	3.0	
5.0	3.0	12.3	12.4	3.0	
6.0	3.2	12.5	12.6	3.2	
7.0	3.1	12.5	12.6	3.1	
8.0	2.8	12.2	12.1	2.8	
9.0	2.3	12.0	12.1	2.3	
10.0					

Articles

SN 2100 LED J/SV

Colors	Polycarbonat
Art. no.	101264360


ceiling mounting Light colour: 6500 K Protection category: IP40



SN 2100 LED J/SV


Colors	Polycarbonat	RAL (special)
Art. no.	101265067	101265269

ceiling mounting Light colour: 6500 K Protection category: IP65



chain mounting adapter SN 2100

Art. no. 100923042



Name	Accessories	Art. no.
J - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420267
LED replacement kit SN 2100	Ersatzteil	101942754
chain mounting adapter SN 2100	optional	100923042
clear cover SN 2100 LED	Ersatzteil	100612541

