




Universal LED downlight for mounting height up to 18m, ideal for illumination of 3m – 4m wide escape routes. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.



Technical data

Material:	polycarbonate	Protection class:	III
Illuminant:	4 x 1W LED-module	Input terminals:	2.5mm ² feed through wiring
Luminous flux:	329 lm	Temperature ta:	-15...+40 °C
Nominal voltage DC:	24 V ±25 %	Impact resistance:	IK06
Nominal current DC:	210 mA		



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Mounting height [m]	Escape route width [m]	Escape route width [m]	Maximum escape route width for area illumination with 1.25lx
8.0	7.1	18.0	
9.0	7.6	20.5	
10.0	8.0	21.6	
11.0	8.2	22.5	
12.0	7.0	21.1	
13.0	7.1	22.2	
14.0	7.1	22.6	
15.0	7.0	23.3	
16.0	7.4	24.6	
17.0	6.8	24.7	
18.0	6.4	24.6	

Articles


SN 2100 TB LED 24V

Colors	Polycarbonat
Art. no.	101344687


SN 2100 TB LED 24V

Colors	Polycarbonat
Art. no.	101344586

ceiling mounting Light colour: 6500 K Protection category: IP40




ceiling mounting Light colour: 6500 K Protection category: IP65



chain mounting adapter SN 2100

Art. no. 100923042



Name	Accessories	Art. no.
ILD 24/4-CC-320-C	Ersatzteil	101425321
LED replacement kit SN 2100 TB	Ersatzteil	101944471
clear cover SN 2100 LED	Ersatzteil	100612541