




Universal LED downlight for mounting height up to 18m, ideal for illumination of 3m – 4m wide escape routes. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.



### Technical data

<b>Material:</b>	polycarbonate	<b>Effective power:</b>	5,1 W
<b>Illuminant:</b>	replaceable 4 x 1W LED-module	<b>Protection class:</b>	III
<b>Luminous flux:</b>	329 lm	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal voltage DC:</b>	24 V ±25 %	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current DC:</b>	210 mA	<b>Impact resistance:</b>	IK06




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Height [m]	Width [m]	Area [m <sup>2</sup> ]	Maximum escape route width for area illumination with 1.25lx
8.0	7.1	18.0	3m
9.0	7.6	20.5	3m
10.0	8.0	21.6	3m
11.0	8.2	22.5	3m
12.0	7.0	21.1	3m
13.0	7.1	22.2	3m
14.0	7.1	22.6	3m
15.0	7.0	23.3	3m
16.0	7.4	24.6	3m
17.0	6.8	24.7	3,5m
18.0	6.4	24.6	3,5m

### Articles


#### SN 2100 TB LED 24V

Colors	Polycarbonat
Art. no.	101344687
ceiling mounting	Light colour: 6500 K Protection category: IP40



#### SN 2100 TB LED 24V

Colors	Polycarbonat	RAL (special)
Art. no.	101344586	104753027
ceiling mounting	Light colour: 6500 K	Protection category: IP65



Name	Accessories	Art. no.
ILD 24/4-CC-320-C	spare part	101425321
LED replacement kit SN 2100 TB	spare part	101944471
clear cover SN 2100 LED	spare part	100612541