




Universal LED downlight for mounting height up to 18m, ideal for illumination of 3m – 4m wide escape routes. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.



Technical data

Material:	polycarbonate	Apparent power:	8,3 VA
Illuminant:	replaceable 4 x 1W LED-module	Effective power:	7,4 W
Luminous flux:	329 lm	Inrush current:	8 A / 50 µs
Nominal voltage AC:	230V ±10% 50/60 Hz	Protection class:	II
Nominal voltage DC:	176 - 264 V	Input terminals:	2.5mm ² feed through wiring
Nominal current AC:	36 mA	Temperature ta:	-15...+40 °C
Nominal current DC:	32 mA	Impact resistance:	IK06




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Mounting height [m]	Beam diameter [m]	Beam diameter [m]	Maximum escape route width for area illumination with 1.25lx
8.0	7.1	18.0	
9.0	7.6	20.5	
10.0	8.0	21.6	
11.0	8.2	22.5	
12.0	7.0	21.1	
13.0	7.1	22.2	
14.0	7.1	22.6	
15.0	7.0	23.3	
16.0	7.4	24.6	
17.0	6.8	24.7	
18.0	6.4	24.6	

Articles


SN 2100 TB LED J/SV		
Colors	Polycarbonat	
Art. no.	101269010	
ceiling mounting	Light colour: 6500 K	Protection category: IP40



SN 2100 TB LED J/SV		
Colors	Polycarbonat	
Art. no.	100748442	
ceiling mounting	Light colour: 6500 K	Protection category: IP65



chain mounting adapter SN 2100	Art. no. 100923042
--------------------------------	--------------------



Name	Accessories	Art. no.
J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267
LED replacement kit SN 2100 TB	spare part	101944471
chain mounting adapter SN 2100	optional	100923042
clear cover SN 2100 LED	spare part	100612541