




Universal LED downlight for mounting height up to 18m, ideal for illumination of 3m – 4m wide escape routes. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.



Technical data

Material:	polycarbonate
Illuminant:	replaceable 4 x 1W LED-module
Luminous flux:	329 lm
Nominal voltage AC:	230V AC $\pm 10\%$ 50/60 Hz
Nominal current AC:	36 mA
Apparent power:	8,3 VA

Effective power:	7,4 W
Inrush current:	8 A / 50 μ s
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK06




Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Height [m]	Beam width [m]	Beam width [m]	Maximum escape route width for area illumination with 1.25lx
8.0	7.1	18.0	
9.0	7.6	20.5	
10.0	8.0	21.6	
11.0	8.2	22.5	
12.0	7.0	21.1	
13.0	7.1	22.2	
14.0	7.1	22.6	
15.0	7.0	23.3	
16.0	7.4	24.6	
17.0	6.8	24.7	
18.0	6.4	24.6	

Articles


SN 2100 TB LED NE/SV

Colors	Polycarbonat
Art. no.	101269212
ceiling mounting	Light colour: 6500 K Protection category: IP40



SN 2100 TB LED NE/SV

Colors	Polycarbonat
Art. no.	100748644
ceiling mounting	Light colour: 6500 K Protection category: IP65



Name	Accessories	Art. no.
LED replacement kit SN 2100 TB	spare part	101944471
NE-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420570
clear cover SN 2100 LED	spare part	100612541