




Universal LED downlight ideal for escape route illumination. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.

**Technical data**

<b>Material:</b>	polycarbonate
<b>Illuminant:</b>	replaceable 4 x 1W LED-module
<b>Luminous flux:</b>	347 lm
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	27 mA
<b>Nominal current DC:</b>	28 mA

<b>Apparent power:</b>	6,3 VA
<b>Effective power:</b>	6,0 W
<b>Inrush current:</b>	6 A / 22 µs
<b>Protection class:</b>	II
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C
<b>Impact resistance:</b>	IK05



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam angle	2.5	3.5	9.9	9.8	4.0
3.0	4.0	9.9	10.6	4.2	
4.0	4.8	10.9	11.9	4.6	
5.0	4.8	12.6	12.7	4.8	
6.0	4.6	13.7	13.2	4.7	
7.0	4.3	13.6	13.5	4.4	
8.0	3.6	13.4	13.4	3.8	
9.0	2.5	13.0	13.0	2.7	


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Beam angle	2.5	2.7	8.4	8.5	2.7
3.0	2.9	9.1	9.2	2.9	
4.0	3.0	10.4	10.5	3.0	
5.0	3.0	11.5	11.6	3.0	
6.0	3.0	12.3	12.4	3.0	
7.0	3.2	12.5	12.6	3.2	
8.0	3.1	12.5	12.6	3.1	
9.0	2.8	12.2	12.1	2.8	
10.0	2.3	12.0	12.1	2.3	


**Articles**

<b>SN 2130 FLD 230V</b>		
Colors	Polycarbonat	
Art. no.	101375710	
ceiling mounting	Light colour: 6500 K	Protection category: IP40

<b>SN 2130 FLD 230V</b>		
Colors	Polycarbonat	
Art. no.	101375811	
ceiling mounting	Light colour: 6500 K	Protection category: IP65



**Frame for recessed ceilingmounting 2130** Art. no. 101428856



Name	Accessories	Art. no.
Cover SN 2130, clear	spare part	100612844
Cover-sticker for 2130 / 2718, white	required	101199894
FLD 230/4 - CC - 320 - L	spare part	101965083
Frame for recessed ceilingmounting 2130	optional	101428856
LMC SN 2130 / SNP 2230 LED Modul und Umrüstsatz	spare part	101943360
Piktogrammscheibe 2130 PL /PR 5mm		101429260
Piktogrammscheibe 2130 PL /PR 5mm		101453815
Piktogrammscheibe 2130 PU /PU 5mm		101429159
Piktogrammscheibe 2130 PU /PU 5mm		101453714

## Info:

