




Universal LED downlight ideal for escape route illumination. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.



Technical data

Material:	polycarbonate
Illuminant:	4 x 1W LED-module
Luminous flux:	347 lm
Nominal voltage DC:	24 V ±20 %

Nominal current DC:	200 mA
Protection class:	III
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Height (m)	1.0lx	1.5lx	2.0lx	3.0lx	4.0lx
2.5	3.7	10.3	9.9	4.0	
3.0	4.1	10.6	10.8	4.3	
4.0	4.9	11.2	12.0	4.6	
5.0	4.9	13.0	12.8	4.8	
6.0	4.8	13.9	13.3	4.7	
7.0	4.5	14.0	13.6	4.4	
8.0	3.9	13.9	13.5	3.8	
9.0	3.0	13.5	13.1	2.8	



Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Height (m)	1.0lx	1.5lx	2.0lx	3.0lx	4.0lx
2.5	2.7	8.4	8.5	2.7	
3.0	2.9	9.1	9.2	2.9	
4.0	3.0	10.4	10.5	3.0	
5.0	3.0	11.5	11.6	3.0	
6.0	3.0	12.3	12.4	3.0	
7.0	3.2	12.5	12.6	3.2	
8.0	3.1	12.5	12.6	3.1	
9.0	2.8	12.2	12.1	2.8	
10.0	2.3	12.0	12.1	2.3	

Articles

SN 2130 LED 24V		
Colors	Polycarbonat	
Art. no.	101353377	
ceiling mounting	Light colour: 6500 K	Protection category: IP40

SN 2130 LED 24V		
Colors	Polycarbonat	
Art. no.	101353478	
ceiling mounting	Light colour: 6500 K	Protection category: IP65



Frame for recessed ceilingmounting 2130 Art. no. 101428856

Name	Accessories	Art. no.
Frame for recessed ceilingmounting 2130	optional	101428856

