

**230V****SN 2130 Polycarbonate luminaires****J/SV**

For connection to JOKER-central battery systems




Universal LED downlight ideal for escape route illumination. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.

**Technical data**

<b>Material:</b>	polycarbonate
<b>Illuminant:</b>	4 x 1W LED-module
<b>Luminous flux:</b>	347 lm
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	36 mA
<b>Nominal current DC:</b>	32 mA

<b>Apparent power:</b>	8,3 VA
<b>Effective power:</b>	7,4 W
<b>Inrush current:</b>	8 A / 50 µs
<b>Protection class:</b>	II
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Distance [m]	2.5	3.7	10.3	9.9	4.0
2.5	3.7	10.3	9.9	4.0	
3.0	4.1	10.6	10.8	4.3	
4.0	4.9	11.2	12.0	4.6	
5.0	4.9	13.0	12.8	4.8	
6.0	4.8	13.9	13.3	4.7	
7.0	4.5	14.0	13.6	4.4	
8.0	3.9	13.9	13.5	3.8	
9.0	3.0	13.5	13.1	2.8	


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

Distance [m]	2.5	2.7	8.4	8.5	2.7
2.5	2.7	8.4	8.5	2.7	
3.0	2.9	9.1	9.2	2.9	
4.0	3.0	10.4	10.5	3.0	
5.0	3.0	11.5	11.6	3.0	
6.0	3.0	12.3	12.4	3.0	
7.0	3.2	12.5	12.6	3.2	
8.0	3.1	12.5	12.6	3.1	
9.0	2.8	12.2	12.1	2.8	
10.0	2.3	12.0	12.1	2.3	

**Articles****SN 2130 LED J/SV**



Colors	Polycarbonat
Art. no.	101271030

ceiling mounting      Light colour: 6500 K      Protection category: IP40

**SN 2130 LED J/SV**

Colors	Polycarbonat
Art. no.	101271333

ceiling mounting      Light colour: 6500 K      Protection category: IP65

**Frame for recessed ceilingmounting 2130      Art. no. 101428856**

Subject to technical changes! Due to component tolerances measured values may vary!

www.inotec-licht.de



2023.10.21

## SN 2130 Polycarbonate luminaires

For connection to JOKER-central battery systems

Name	Accessories	Art. no.
Cover SN 2130, clear	Ersatzteil	100612844
Cover-sticker for 2130 / 2718, white	required	101199894
Frame for recessed ceilingmounting 2130	optional	101428856
J - ET 9 / 24 SV -max.24VDC,320mAconst	Ersatzteil	101420267
LED replacement kit SN 2130 /SNP 2230	Ersatzteil	101943360
Piktogrammscheibe 2130 PL /PR 5mm		101429260
Piktogrammscheibe 2130 PL /PR 5mm		101453815
Piktogrammscheibe 2130 PU /PU 5mm		101429159
Piktogrammscheibe 2130 PU /PU 5mm		101453714

### Info:

