




Universal LED downlight ideal for escape route illumination. UV resistant, heat filament tested polycarbonate housing with optional side cable entry and comfortable installation space.



Technical data

Material:	polycarbonate
Illuminant:	replaceable 4 x 1W LED-module
Luminous flux:	347 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	36 mA
Nominal current DC:	32 mA

Apparent power:	8,3 VA
Effective power:	7,4 W
Inrush current:	8 A / 50 µs
Protection class:	II
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK05



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8



| Beam diameter (mm) |
|--------------------|--------------------|--------------------|--------------------|--------------------|
| 2.5 | 3.5 | 9.9 | 9.8 | 4.0 |
| 3.0 | 4.0 | 9.9 | 10.6 | 4.2 |
| 4.0 | 4.8 | 10.9 | 11.9 | 4.6 |
| 5.0 | 4.8 | 12.6 | 12.7 | 4.8 |
| 6.0 | 4.6 | 13.7 | 13.2 | 4.7 |
| 7.0 | 4.3 | 13.6 | 13.5 | 4.4 |
| 8.0 | 3.6 | 13.4 | 13.4 | 3.8 |
| 9.0 | 2.5 | 13.0 | 13.0 | 2.7 |

| Beam diameter (mm) |
|--------------------|--------------------|--------------------|--------------------|--------------------|
| 2.5 | 2.7 | 8.4 | 8.5 | 2.7 |
| 3.0 | 2.9 | 9.1 | 9.2 | 2.9 |
| 4.0 | 3.0 | 10.4 | 10.5 | 3.0 |
| 5.0 | 3.0 | 11.5 | 11.6 | 3.0 |
| 6.0 | 3.0 | 12.3 | 12.4 | 3.0 |
| 7.0 | 3.2 | 12.5 | 12.6 | 3.2 |
| 8.0 | 3.1 | 12.5 | 12.6 | 3.1 |
| 9.0 | 2.8 | 12.2 | 12.1 | 2.8 |
| 10.0 | 2.3 | 12.0 | 12.1 | 2.3 |


Articles

SN 2130 LED J/SV		
Colors	Polycarbonat	
Art. no.	101271030	
ceiling mounting	Light colour: 6500 K	Protection category: IP40

SN 2130 LED J/SV		
Colors	Polycarbonat	
Art. no.	101271333	
ceiling mounting	Light colour: 6500 K	Protection category: IP65



Frame for recessed ceilingmounting 2130 Art. no. 101428856



Name	Accessories	Art. no.
Cover SN 2130, clear	spare part	100612844
Frame for recessed ceilingmounting 2130	optional	101428856
J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267
LMC SN 2130 / SNP 2230 LED Modul und Umrüstsz	spare part	101943360

Info:

PO:	PR:	PU:	PL:	PRO:	PRU:	PLU:	PLO:

