

230V**SN 6114.1 O** Wall, floor and stair luminaires**J/SV**

For connection to JOKER-central battery systems




Robust LED safety luminaires to illuminate steps or escape routes. Recessed wall and stair mounting. Made of high-quality die-cast aluminium with high protection category.

Technical data


Material:	die-cast aluminium
Illuminant:	18 x 0,15W LED-module
Luminous flux:	169 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	27 mA
Nominal current DC:	22 mA

Apparent power:	6,2 VA
Effective power:	5,2 W
Inrush current:	8 A / 50 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C

**Articles****SN 6114.1 LED J/SV**


Colors	RAL 9005	RAL (special)
Art. no.	104434442	104434543

recessed wall or stair mounting Light colour: 3000 K Protection category: IP54

**SN 6114.1 LED J/SV**

Colors	RAL 9005	RAL (special)
Art. no.	104435654	104435755

recessed wall or stair mounting Light colour: 4000 K Protection category: IP54



Name	Accessories	Art. no.
LM 176x20 18/3K KL	Ersatzteil	104412113
LM 176x20 18/4K KL	Ersatzteil	104412012

