




Robust LED safety luminaires to illuminate steps or escape routes. Recessed wall and stair mounting. Made of high-quality die-cast aluminium with high protection category.

Technical data

Material:	die-cast aluminium
Illuminant:	3 x 1W LED-module
Luminous flux:	25 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	23 mA
Nominal current DC:	22 mA



Apparent power:	5,2 VA
Effective power:	4,9 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Articles

SN 6114 G FLD 230V grids		
Colors	RAL 9005	RAL (special)
Art. no.	101373383	101373484
recessed wall or stair mounting	Light colour: 6500 K	Protection category: IP54

recessed box for concrete wallinstall. Art. no. 101070966



Name	Accessories	Art. no.
	optional	101070966




Robust LED safety luminaires to illuminate steps or escape routes. Recessed wall and stair mounting. Made of high-quality die-cast aluminium with high protection category.

Technical data

Material:	die-cast aluminium
Illuminant:	3 x 1W LED-module
Luminous flux:	93 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	23 mA
Nominal current DC:	22 mA



Apparent power:	5,2 VA
Effective power:	4,9 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C



Articles

SN 6114 O FLD 230V		
Colors	RAL 9005	RAL (special)
Art. no.	101373181	101373282
recessed wall or stair mounting	Light colour: 6500 K	Protection category: IP54

recessed box for concrete wallinstall. Art. no. 101070966



Name	Accessories	Art. no.
	optional	101070966