




Robust LED safety luminaires to illuminate steps or escape routes. Recessed wall and stair mounting. Made of high-quality die-cast aluminium with high protection category.

Technical data


Material:	die-cast aluminum	Nominal current DC:	150 mA
Illuminant:	3 x 1W LED-module	Protection class:	III
Luminous flux:	25 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C



Articles


SN 6114 G LED 24V grids

Colors	RAL 9005	
Art. no.	101328927	
recessed wall or stair mounting	Light colour: 6500 K	Protection category: IP54



recessed box for concrete wallinstall.

Art. no. 101070966




Name	Accessories	Art. no.
	optional	101070966



Robust LED safety luminaires to illuminate steps or escape routes. Recessed wall and stair mounting. Made of high-quality die-cast aluminium with high protection category.

Technical data


Material:	die-cast aluminium	Nominal current DC:	150 mA
Illuminant:	3 x 1W LED-module	Protection class:	III
Luminous flux:	93 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C



Articles


SN 6114 O LED 24V

Colors	RAL 9005	RAL (special)
Art. no.	101329028	102160804
recessed wall or stair mounting	Light colour: 6500 K	Protection category: IP54



recessed box for concrete wallinstall.

Art. no. 101070966



Name	Accessories	Art. no.
	optional	101070966