

Luminaire with targeted light output. Robust trapezoidal luminaire housing for wall mounting made of powder-coated die-cast aluminium. High protection rating for outdoor installation. And optional cable entry at the side.


**Technical data**

<b>Material:</b>	die-cast aluminum powder-coated
<b>Illuminant:</b>	replaceable 18 x 0,3W LED-module
<b>Luminous flux:</b>	687 lm
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	40 mA
<b>Nominal current DC:</b>	35 mA

<b>Apparent power:</b>	9,3 VA
<b>Effective power:</b>	9,0 W
<b>Inrush current:</b>	6 A / 22 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C
<b>Impact resistance:</b>	IK09

**Technical data (General lighting)**

<b>Luminous flux:</b>	687 lm
-----------------------	--------



Wall mounting: Minimum illumination 1.0lx

Bollard console (0.8m)	Distance to middle of escape route					
	1.0m		2.0m		3.0m	
1.0	2.9	6.9	2.8	7.3	1.7	6
1.5	3.6	8.7	3.7	9.2	3.2	8.7
2.0	4.2	10.0	4.3	10.6	4	10.4
2.5	4.6	11.2	4.8	11.7	4.6	11.7
3.0	5.0	12.2	5.2	12.7	5.0	12.8
3.5	5.3	13.0	5.6	13.6	5.4	13.8
4.0	5.6	13.8	5.8	14.4	5.8	14.6
4.5	5.8	14.5	6.1	15.1	6.0	15.4
5.0	6.0	15.1	6.3	15.7	6.2	16.0
5.5	6.1	15.6	6.4	16.2	6.4	16.6
6.0	6.2	16.0	6.5	16.7	6.6	17.0

**Articles**


**SN 6201 -06 FLD 230V**

Colors	DB 703	HWF 7015	RAL 7015	RAL 9016	HWF 9016	HWF (special)
Art. no.	104362300	104362502	104362195	104362094	104362401	104362603

wall mounting


Light colour: 3000 K

Protection category: IP65




**mounting adapter 6201 RAL 7015**

Art. no. 104575292




**Anchor plate bollard console6201**

Art. no. 104892665

**Pollerkonsole 6201 RAL 7015**

Art. no. 104927728



Name	Accessories	Art. no.
Anchor plate bollard console6201	optional	104892665
FLD 230/8 – CC – 650 – C	spare part	100903440
LM 176x20 18/3K KB150 LED Modul	spare part	104412113
Pollerkonsole 6201 RAL 7015	optional	104927728
mounting adapter 6201 RAL 7015	optional	104575292