


Luminaire with targeted light output. Robust trapezoidal luminaire housing for wall mounting made of powder-coated die-cast aluminium. High protection rating for outdoor installation. And optional cable entry at the side.

Technical data

Material:	die-cast aluminum powder-coated	Effective power:	7,1 W
Illuminant:	replaceable 18 x 0,3W LED-module	Protection class:	I
Luminous flux:	687 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C
Nominal current DC:	295 mA	Impact resistance:	IK09

Technical data (General lighting)

Luminous flux:	687 lm
-----------------------	--------




Wall mounting: Minimum illumination 1.0lx


Bollard console (0.8m)	Distance to middle of escape route					
	1.0m		2.0m		3.0m	
	2.6	6.1	2.2	6.1	-	4.3
1.0	2.9	6.9	2.8	7.3	1.7	6
1.5	3.6	8.7	3.7	9.2	3.2	8.7
2.0	4.2	10.0	4.3	10.6	4	10.4
2.5	4.6	11.2	4.8	11.7	4.6	11.7
3.0	5.0	12.2	5.2	12.7	5.0	12.8
3.5	5.3	13.0	5.6	13.6	5.4	13.8
4.0	5.6	13.8	5.8	14.4	5.8	14.6
4.5	5.8	14.5	6.1	15.1	6.0	15.4
5.0	6.0	15.1	6.3	15.7	6.2	16.0
5.5	6.1	15.6	6.4	16.2	6.4	16.6
6.0	6.2	16.0	6.5	16.7	6.6	17.0

Articles


SN 6201 -06 LED 24V/S						
Colors	DB 703	HWF 7015	RAL 7015	RAL 9016	HWF 9016	HWF (special)
Art. no.	104360983	104361185	104360781	104360680	104361084	104361286
wall mounting	Light colour: 3000 K		Protection category: IP65			




mounting adapter 6201 RAL 7015 Art. no. 104575292



Anchor plate bollard console6201 Art. no. 104892665



Pollerkonsole 6201 RAL 7015 Art. no. 104927728



Name	Accessories	Art. no.
Anchor plate bollard console6201	optional	104892665
L-JET 7/S-max. 24V DC650mA const	spare part	101422691
LM 176x20 18/3K KB150 LED Modul	spare part	104412113
Pollerkonsole 6201 RAL 7015	optional	104927728
mounting adapter 6201 RAL 7015	optional	104575292