


Trapezoidal LED emergency luminaires for illumination of escape routes and exit doors. Luminaires for wall mounting with elegant powder coated metal housing without any visible screws.

Technical data

Material:	sheet steel powder-coated	Nominal current DC:	150 mA
Illuminant:	3 x 1W LED-module	Protection class:	III
Luminous flux:	210 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±20 %	Temperature ta:	-15...+40 °C





Wall mounting: Minimum illumination 1.0lx

Distance to middle of escape route	Distance to middle of escape route					
	1.0m		2.0m		3.0m	
1.0	2.2	5.4	2.3	5.7	1.8	5.2
2.0	2.8	7.0	2.8	7.2	2.3	6.8
2.5	3.0	7.4	3.0	7.8	2.6	7.4
3.0	3.1	8.0	3.1	8.4	2.7	8.1
3.5	3.2	8.5	3.2	8.7	2.8	8.5
4.0	3.1	8.7	3.1	9.1	2.8	8.8
4.5	3.0	9.0	3.0	9.3	2.7	9.0
5.0	2.8	9.0	2.8	9.3	2.5	9.1
5.5	2.6	9.0	2.6	9.3	2.0	9.1
6.0	2.2	8.8	2.1	9.2	1.5	8.9

Articles



SN 6204.1 LED 24V

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101331856	101331654	101331957
wall mounting	Light colour: 6500 K		Protection category: IP40



mounting adapter SN 6204.1 IP40, RAL 9016

Art. no. 101444317



Name	Accessories	Art. no.
mounting adapter SN 6204.1 IP40, RAL 9016	optional	101444317