


Ball-impact and shock resistant LED safety luminaire with optimised light distribution for the illumination of areas. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



**Technical data**

<b>Material:</b>	sheet steel powder-coated
<b>Illuminant:</b>	1 x 3,5W LED-module
<b>Luminous flux:</b>	434 lm
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz
<b>Nominal voltage DC:</b>	176 - 264 V
<b>Nominal current AC:</b>	25 mA
<b>Nominal current DC:</b>	25 mA

<b>Apparent power:</b>	5,8 VA
<b>Effective power:</b>	5,5 W
<b>Inrush current:</b>	6 A / 22 µs
<b>Protection class:</b>	I
<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Temperature ta:</b>	-15...+40 °C
<b>Impact resistance:</b>	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

2.5	5.3	13.4	
3.0	5.4	14.2	
3.5	5.5	15.0	
4.0	5.5	15.1	
4.5	5.4	15.5	
5.0	5.0	15.5	


Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8

2.5	4.4	11.8	
3.0	4.5	13.0	
3.5	4.4	13.9	
4.0	4.3	14.4	
4.5	3.8	14.9	
5.0	3.4	15.3	

**Articles**


<b>SN 8030.2 AP -12 SLB FLD 230V</b>			
Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	104239634	104239533	104239735

ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP40



<b>SN 8030.2 D -12 SLB FLD 230V</b>			
Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	104238624	104238523	104238725

ceiling mounting Light colour: 4000 K Protection category: IP40



Name	Accessories	Art. no.
FLD 230/4 - CC - 320 - L	spare part	101965083
LM 8030.2 1(12V)/4K SLB 24V RAL9016 LED Modul	spare part	104487487