




Ball-impact and shock resistant LED safety luminaire with optimised light distribution for the illumination of areas. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



### Technical data

<b>Material:</b>	sheet steel powder-coated	<b>Effective power:</b>	4,6 W
<b>Illuminant:</b>	1 x 3,5W LED-module	<b>Protection class:</b>	III
<b>Luminous flux:</b>	434 lm	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal voltage DC:</b>	24 V ±25 %	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current DC:</b>	190 mA	<b>Impact resistance:</b>	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8

Beam diameter (m)	Beam length (m)	Beam length (m)
2.5	5.3	13.4
3.0	5.4	14.2
3.5	5.5	15.0
4.0	5.5	15.1
4.5	5.4	15.5
5.0	5.0	15.5

Minimum illumination 1.0lx (area illumination), Maintenance factor 0.8


Beam diameter (m)	Beam length (m)	Beam length (m)
2.5	4.4	11.8
3.0	4.5	13.0
3.5	4.4	13.9
4.0	4.3	14.4
4.5	3.8	14.9
5.0	3.4	15.3

### Articles

#### SN 8030.2 AP -12 SLB LED 24V

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	104419789	104419890	104419991


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP40



#### SN 8030.2 D -12 SLB LED 24V

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	104420904	104421005	104421106

ceiling mounting Light colour: 4000 K Protection category: IP40



Name	Accessories	Art. no.
ILD 24/4-CC-320-C	spare part	101425321
LM 8030.2 1(12V)/4K SLB 24V RAL9016 LED Modul	spare part	104487487