




Ball-impact and shock resistant LED safety luminaire with optimised light distribution for the illumination of escape routes. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



Technical data

Material:	sheet steel powder-coated
Illuminant:	1 x 0,9W LED-module
Luminous flux:	116 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	13 mA
Nominal current DC:	12 mA

Apparent power:	3,0 VA
Effective power:	2,6 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Beam diameter (m)	2.5	4.4	13.6	4.9	1.8
3.0	4.5	13.9	5.0	1.7	
3.5	4.4	12.6	5.0	1.5	
4.0	3.9	12.6	4.9	1.2	
4.5	2.9	12.6	4.7	0.8	

Articles

SN 8030.2 AP -03 ALB FLD 230V

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101834438	101834337	104239129


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP40



SN 8030.2 D -03 ALB FLD 230V

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101834135	101834034	101834236

ceiling mounting Light colour: 4000 K Protection category: IP40



Name	Accessories	Art. no.
FLD 230/4 - CC - 320 - L	spare part	101965083
LM 8030.2 1(3V)/4K ALB 24V RAL9016 LED Modul	spare part	104487588
LM 8030.2 E 1(3V)/4K ALB 24V RAL9016 LED Modul	spare part	104489410