




Ball-impact and shock resistant LED safety luminaire with optimised light distribution for the illumination of escape routes. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



Technical data

Material:	sheet steel powder-coated	Effective power:	2,0 W
Illuminant:	1 x 0,9W LED-module	Protection class:	III
Luminous flux:	116 lm	Input terminals:	2.5mm ² feed through wiring
Nominal voltage DC:	24 V ±25 %	Temperature ta:	-15...+40 °C
Nominal current DC:	80 mA	Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Beam diameter (m)	2.5	3.0	3.5	4.0	4.5
Beam diameter (m)	2.5	3.0	3.5	4.0	4.5
Beam diameter (m)	4.4	4.5	4.4	3.9	2.9
Beam diameter (m)	13.6	13.9	12.6	12.6	12.6
Beam diameter (m)	4.9	5.0	5.0	4.9	4.7
Beam diameter (m)	1.8	1.7	1.5	1.2	0.8

Articles

SN 8030.2 AP -03 ALB LED 24V

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101833226	101833125	101833327


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP40



SN 8030.2 D -03 ALB LED 24V

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101832923	101832822	101833024

ceiling mounting Light colour: 4000 K Protection category: IP40



Name	Accessories	Art. no.
ILD 24/4-CC-320-C	spare part	101425321
LM 8030.2 1(3V)/4K ALB 24V RAL9016 LED Modul	spare part	104487588