




Ball-impact and shock resistant LED safety luminaire with optimised light distribution for the illumination of escape routes. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



### Technical data

<b>Material:</b>	sheet steel powder-coated	<b>Apparent power:</b>	3,5 VA
<b>Illuminant:</b>	1 x 0,9W LED-module	<b>Effective power:</b>	2,6 W
<b>Luminous flux:</b>	116 lm	<b>Inrush current:</b>	8 A / 50 µs
<b>Nominal voltage AC:</b>	230V ±10% 50/60 Hz	<b>Protection class:</b>	I
<b>Nominal voltage DC:</b>	176 - 264 V	<b>Input terminals:</b>	2.5mm <sup>2</sup> feed through wiring
<b>Nominal current AC:</b>	15 mA	<b>Temperature ta:</b>	-15...+40 °C
<b>Nominal current DC:</b>	12 mA	<b>Impact resistance:</b>	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Mounting height (m)	2.5	4.4	13.6	4.9	1.8
2.5	4.4	13.6	4.9	1.8	
3.0	4.5	13.9	5.0	1.7	
3.5	4.4	12.6	5.0	1.5	
4.0	3.9	12.6	4.9	1.2	
4.5	2.9	12.6	4.7	0.8	

### Articles

#### SN 8030.2 AP -03 ALB LED J/SV

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101831408	101831307	101831509


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP40



#### SN 8030.2 D -03 ALB LED J/SV

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	101831105	101831004	101831206

ceiling mounting Light colour: 4000 K Protection category: IP40



Name	Accessories	Art. no.
J-ET 9/24 SVmax.24VDC,320mAconst	spare part	101420267
LM 8030.2 1(3V)/4K ALB 24V RAL9016 LED Modul	spare part	104487588