





Ball-impact and shock resistant LED safety luminaire with optimised light distribution for the illumination of escape routes. Powder-coated aluminium housing with slim design, perfect for use in environments with high mechanical stresses and in sports facilities.



Technical data

Material:	sheet steel powder-coated
Illuminant:	1 x 1,8W LED-module
Luminous flux:	248 lm
Nominal voltage AC:	230V ±10% 50/60 Hz
Nominal voltage DC:	176 - 264 V
Nominal current AC:	17 mA
Nominal current DC:	16 mA

Apparent power:	3,9 VA
Effective power:	3,6 W
Inrush current:	6 A / 22 µs
Protection class:	I
Input terminals:	2.5mm ² feed through wiring
Temperature ta:	-15...+40 °C
Impact resistance:	IK10



Ceiling mounting: Minimum illumination 1.0lx (middle of escape route), Maintenance factor 0.8


Mounting height (m)	1.0m	1.5m	2.0m	2.5m	3.0m
5.0	6.0	14.6	4.8	1.9	
6.0	6.2	15.8	4.9	2.1	
7.0	6.3	16.8	5.3	2.2	
8.0	5.8	17.5	5.7	2.3	
9.0	5.4	17.9	6.0	2.3	
10.0	4.9	17.7	6.3	2.1	
11.0	4.0	16.9	6.5	1.6	

Articles

SN 8030.2 AP -06 AHB FLD 230V

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	104239331	104239230	104239432


ceiling mounting for exposed wiring Light colour: 4000 K Protection category: IP40



SN 8030.2 D -06 AHB FLD 230V

Colors	RAL 7015	RAL 9016	RAL (special)
Art. no.	104238321	104238220	104238422

ceiling mounting Light colour: 4000 K Protection category: IP40



Name	Accessories	Art. no.
FLD 230/4 - CC - 320 - L	spare part	101965083
LM 8030.2 1(6V)/4K AHB 24V RAL9016 LED Modul	spare part	104487891